

CS412 Fall11

Prof. Ron

Matlab Assignment #0

Prepared by Narfi Stefansson

Due September 13, 2011

Grace days can not be used for this assignment

The `Matlab` assignments are not intended to be complete tutorials, and they will definitely not explain all the `Matlab` commands you will need in this course. But we will explain a few of the `Matlab` commands here, and point out many others that may be useful.

After this first `Matlab` assignment, you should be familiar with the following commands:

| | |
|----------------------------|---|
| <code>help</code> | <code>helpdesk</code> |
| <code>:</code> (colon) | <code>linspace</code> |
| <code>size</code> | <code>plot</code> |
| <code>print</code> | <code>diary</code> |
| <code>zeros</code> | <code>ones</code> |
| <code>eye</code> | <code>xlabel</code> |
| <code>ylabel</code> | <code>title</code> |
| <code>sin</code> | <code>exp</code> |
| <code>+, -, *</code> | <code>'</code> (transpose) |
| <code>\</code> (backslash) | <code>end</code> (as in <code>x(2:end-1)</code>) |

as well the concepts of:

- matrices
- column vectors
- row vectors
- scripts
- submatrices: `A(ind1, ind2) = ...`
- calling a function
- creating a function

If you are familiar with `Matlab` as well as with the above `Matlab` commands, skip the preface and go directly to the last page, where the actual assignment is to be found. Otherwise, keep on reading.

Preface

To start `matlab`, simply type `Matlab` at the Unix prompt. `Matlab` should then start, and you get the `Matlab` prompt, `>>`.

The most important commands in `Matlab` are:

- `help`

- `helpwin`
- `helpdesk`

The first command gives you help inside `Matlab`. The second command gives you a separate window with the help texts, and the third command starts Netscape and gives you access to the extensive HTML help that comes with `Matlab`. If you type in `help helpdesk` at the `Matlab` prompt, you get:

```
HELPDESK Comprehensive hypertext documentation and troubleshooting.
HELPDESK loads the main MATLAB Help Desk page into the Web browser.
```

Try the following:

```
a=1
size(a)
```

and compare the output with:

```
a=1;
size(a);
```

The commands do the same, but the `;` (semicolon) suppresses printing. You just defined `a` to be a 1-by-1 matrix. To type in larger matrices, type them in row by row, and use spaces or commas between elements, and use `;` to separate rows. E.g.

```
A = [1,2,3;4,5,6];
```

To look at the contents of the variable `A`, just type it in at the `Matlab` prompt:

```
A
gives:
```

```
A =
```

```
     1     2     3
     4     5     6
```

You can access the elements of `A` through regular indexing: `A(2,3)` would give you 6 here.

You can only use an index that exceeds the dimensions of `A` if you are assigning a value to `A`. `Matlab` will not complain about:

```
A(2, 5) = 1000
```

But if you try to get the value of an element that doesn't exist:

```
A(100, 100)
```

`Matlab` will complain.

- `:` (the colon operator)

The `:` can be used in two ways: To create sequences and for indexing. `1:10` gives the sequence

```
1     2     3     4     5     6     7     8     9    10
```

The other way of using the colon is to gain access to all rows or columns of a matrix.

```
A(1,:)

```

means: the 1st row of `A` and all columns. Similarly `A(:, 2)` means: all rows of `A`, and the 2nd column.

- `end`

The keyword `end` is useful for indexing (and other things). Look at the following:

```
x = 1:10;
x(3:end) = 7
```

```
1     2     7     7     7     7     7     7     7     7
```

so here

```
3:end
```

refers to elements 3 to the end of `x`. You can also use e.g.

```
end - 1
```

to refer to the second last element of `x`.

- `diary`

The `diary` command saves the text of your `Matlab` session. `diary on` causes `Matlab` to save all input and most of the output to the file named `diary` until you give the command `diary off`. `diary 000126` will save the input/output in the file `000126`.

- `linspace`
- `plot`

The `linspace` command stands for linearly spaced and is especially useful when generating graphs. Try the following:

```
x = linspace(0,4,50); plot(x, exp(-x))
```

to see the graph of $x \mapsto e^{-x}$. In general, if `x` and `y` are vectors of the same length, `plot(x,y)` plots the vector `y` versus the vector `x`, and `plot(y)` plots the vector `y` against the vector `1:length(y)`.

You can decorate your graphs even further by using:

- `xlabel`
- `ylabel`
- `title`

and use single quote characters to enclose the string:

```
xlabel('The x-axis')
```

```
ylabel('The y-axis')
```

```
title('The title')
```

It's easy to print to a file in `Matlab`:

```
print -dps myfig.ps
```

tells `Matlab` to print the current figure to the file `myfig.ps` (and overwrite the current contents of the file). If you want to append to the file, use

```
print -append -dps myfig.ps
```

The following commands are indispensable when creating matrices:

- `zeros`
- `ones`
- `eye`

`zeros(5,3)` creates a 5-by-3 matrix of zeros, `ones(3,2)` creates a 3-by-2 matrix filled with 1's, and `eye(3,2)` creates the 3-by-2 upper left corner of an identity matrix. If the matrix is to be square, you can use just one argument; e.g., `ones(3)` is the same as `ones(3,3)`.

Matrices are truly the building blocks of `Matlab`, so it comes at no surprise that the arithmetic operators:

- `+`
- `-`
- `*`

work on matrices. Try this:

```
A = [1, 2; 3, 4];
B = [0, 1; 1, 1];
A + B
A - B
A * B
```

and notice that `A * B` gives you the matrix multiplication of `A` and `B`.

It is very easy to solve linear equations in `Matlab`. The `backslash` does the trick.

- `\` (`backslash`)

If `A` is an `n`-by-`n` invertible matrix and `b` is a column vector of length `n`, the solution to

$$Ax = b$$

is given by `A\b`.

The following operation in `Matlab`:

- `'` (`transpose`)

leads us to the next topic.

The most common mistake in `Matlab` is beyond any doubt that of confusing row and column vectors. We normally think of a vector as just a vector, but `Matlab` thinks of it as a matrix. So the question is: is the vector an `n`-by-1 matrix or an 1-by-`n` matrix?

For example, let `A = [1, 2; 3, 4]`; and `b = [1, 0]`;

Then `Matlab` will respond to the command `A*b` by:

```
??? Error using ==> *
Inner matrix dimensions must agree.
```

because `b` is of the size 1-by-2 and not 2-by-1 as it should be. Remember that `size(b)` gives you the size. You can fix this by using any of the following:

- Typing `b` in again, now as a column vector: `b = [0; 1];`
- Transposing `b` by using the transpose operator: `b = b';`.
- Using the colon: `b(:)` returns a column vector, so `b = b(:)`; also does the trick.

The last topic for this introduction to `Matlab` is how you can create your own functions and scripts. Suppose you want to create a function called `myfirst` that accepts two matrices as input arguments and returns their sum. Then you would have to put these commands:

```
function sum = myfirst(v, w)
% sum the two inputs
sum = v + w;
```

into a file called `myfirst.m` in your working directory. Once you have saved it, you can invoke the function:

```
myfirst(1, 0)
myfirst([1, 2], [3, 4])
```

If you look back at the function that you saved in `myfirst.m`, the first line: `function sum = myfirst(v, w)` tells `Matlab` that your function should return the variable `sum`, that its name is `myfirst`, and that it accepts two input arguments. Finally, `Matlab` will print out that percented first line any time you say `help myfirst`.

You should also try to put the following into a file called, say, `firstscript` in your working directory:

```
A = eye(3);
b = ones([3, 1]);
x = A\b;
```

and then type `firstscript` at the `Matlab` prompt. This simply runs the commands in the file.

Remember that more information on `Matlab` can be/will/was obtained from (i) the first class demo, (ii) the `Matlab` primer (at DoIT), (iii) the extensive on-line `help`.

It's time to practice the above notions...

Assignment

1. Generate a plot of the function `sin` on the interval $[-1, 1]$ with an appropriate title. Turn in the figure together with the commands you used to generate the figure.
2. Find the solution to the following 20-by-20 system of equations. Turn in your code and the output.

$$\begin{pmatrix} 1 & \dots & 1 & 0 \\ & 1 & & \\ \vdots & & \ddots & \vdots \\ 1 & \dots & & 1 \end{pmatrix} x = \begin{pmatrix} 17 \\ 0 \\ \vdots \\ 0 \end{pmatrix}$$

[Note: All entries in the matrix not explicitly mentioned are meant to be zero].

3. Create a `Matlab` function called `ssolve` that:
 - (a) Accepts three parameters, a , b , and n , in that order.
 - (b) Returns the solution to the following n by n system:

$$\begin{pmatrix} 1 & a & & & \\ & 1 & & & \\ & & \ddots & & \\ & & & 1 & \\ b & b & \dots & b & 1 \end{pmatrix} x = \begin{pmatrix} 1 \\ 2 \\ \vdots \\ n-2 \\ 0 \\ n \end{pmatrix}$$

as a column vector.

[Note: All entries in the matrix not explicitly mentioned are meant to be zero].

4. Turn in a printout of the function `ssolve` and plots of the vectors
 - (a) `ssolve(10, 0.1, 30)`
 - (b) `ssolve(2, -0.05, 50)`

with the appropriate titles. Also turn in the code that generated these figures.