

## Call Stack Example


```
/***
 * A class used to illustrate how the call stack works.
 */
public class CallStackExample {

    public static void main(String[] args) {
        int x = 7, y = 8;
        String dairy = "milk", soda = "cola";

        SimpleMug mug1 = new SimpleMug(y, dairy); ←
        SimpleMug mug2 = new SimpleMug(x, soda);

        mug1.fill(x);
        y = mug2.getMaxCapacity();
    }
}
```

Memory right before call to SimpleMug constructor



1

## Call Stack Example


```
/***
 * A class used to illustrate how the call stack works.
 */
public class CallStackExample {

    public static void main(String[] args) {
        int x = 7, y = 8;
        String dairy = "milk", soda = "cola";

        SimpleMug mug1 = new SimpleMug(y, dairy); ←
        SimpleMug mug2 = new SimpleMug(x, soda);

        mug1.fill(x);
        y = mug2.getMaxCapacity();
    }
}
```

Memory right before SimpleMug constructor returns to main



2

## Call Stack Example


```
/***
 * A class used to illustrate how the call stack works.
 */
public class CallStackExample {

    public static void main(String[] args) {
        int x = 7, y = 8;
        String dairy = "milk", soda = "cola";

        SimpleMug mug1 = new SimpleMug(y, dairy); ←
        SimpleMug mug2 = new SimpleMug(x, soda); ←

        mug1.fill(x);
        y = mug2.getMaxCapacity();
    }
}
```

Memory right before call to SimpleMug constructor



3

## Call Stack Example


```
/***
 * A class used to illustrate how the call stack works.
 */
public class CallStackExample {

    public static void main(String[] args) {
        int x = 7, y = 8;
        String dairy = "milk", soda = "cola";

        SimpleMug mug1 = new SimpleMug(y, dairy); ←
        SimpleMug mug2 = new SimpleMug(x, soda); ←

        mug1.fill(x);
        y = mug2.getMaxCapacity();
    }
}
```

Memory right before SimpleMug constructor returns to main



4


## Call Stack Example

```
/***
 * A class used to illustrate how the call stack works.
 */
public class CallStackExample {

    public static void main(String[] args) {
        int x = 7, y = 8;
        String dairy = "milk", soda = "cola";
        SimpleMug mug1 = new SimpleMug(y, dairy);
        SimpleMug mug2 = new SimpleMug(x, soda);

        mug1.fill(x);
        y = mug2.getMaxCapacity();
    }
}
```

Memory right before `fill` returns to `main`



5


## Call Stack Example

```
/***
 * A class used to illustrate how the call stack works.
 */
public class CallStackExample {

    public static void main(String[] args) {
        int x = 7, y = 8;
        String dairy = "milk", soda = "cola";
        SimpleMug mug1 = new SimpleMug(y, dairy);
        SimpleMug mug2 = new SimpleMug(x, soda);

        mug1.fill(x);
        y = mug2.getMaxCapacity();
    }
}
```

Memory right before `getMaxCapacity` returns to `main`



6


## Call Stack Example

```
/***
 * A class used to illustrate how the call stack works.
 */
public class CallStackExample {

    public static void main(String[] args) {
        int x = 7, y = 8;
        String dairy = "milk", soda = "cola";
        SimpleMug mug1 = new SimpleMug(y, dairy);
        SimpleMug mug2 = new SimpleMug(x, soda);

        mug1.fill(x);
        y = mug2.getMaxCapacity();
    }
}
```

Memory right before `main` exits



7