# **CS/ECE 252: INTRODUCTION TO COMPUTER ENGINEERING**

# UNIVERSITY OF WISCONSIN—MADISON

Prof. Gurindar Sohi TAs: Annie Lin, Mohit Verma, Neha Mittal, Daniel Griffin, Yuzhe Ma

> Examination 1 In Class (50 minutes) Monday, September 28, 2016 Weight: 17.5%

NO: BOOK(S), NOTE(S), CALCULATORS OR ELECTRONIC DEVICES OF ANY SORT. The exam has nine pages. You must turn in the pages 1-8. Circle your final answers. Plan your time carefully since some problems are longer than others. Use the blank sides of the exam for scratch work.

LAST NAME:	
FIRST NAME:	
Section:	
ID#: _	

Problem	Maximum Points	Points Earned		
1	1			
2	3			
3	2			
4	2			
5	4			
6	4			
7	6			
8	4			
9	4			
10	3			
Total	33			

Which of the following statements are true?

i) In logic circuits, there is only one way to implement any particular function (e.g. addition).

ii) There can be many different microarchitectures implementing a single ISA.

iii) The translation from the unique assembly language of a computer to its ISA is done by an assembler.

Select one answer below:

a) i & ii

b) i & iii

c) ii & iii

d) i, ii & iii

# Problem 2

(3 points)

Match the following computer abstraction layers with their definitions specified in the table.

a) ISA

- b) Program
- c) Algorithm
- d) Microarchitecture
- e) Devices

A step by step procedure that is guaranteed to terminate, such that each step is precisely stated and can be carried out by the computer
The complete specification of the interface between programs that have been written and the underlying computer hardware that must carry out the work of those programs.
Specific hardware technology used to implement logical components of the computer system. (Ex. CMOS/NMOS transistors)
A 'mechanical language' that is used to specify a sequence of instructions to a computer.
A detailed organization of the implementation of an ISA.

(a) What is the difference between high level and low level languages?

(b) Why are natural languages unsuitable for programming on a computer?

#### Problem 4

(2 points)

A class has 185 students enrolled in it. Each student is to be assigned a unique ID number (in unsigned binary notation).

(a) What is the minimum number of bits needed to assign each student a unique binary ID number?

(b) If we were to increase the number of bits by 1, how many more students can be accommodated in the class and still be assigned a unique binary ID number?

(a) Using 8 bits for each number, write the 1's complement, 2's complement, and signed magnitude binary number of the decimal numbers in the table below:

Decimal	1's Complement	2's Complement	Signed Magnitude
19			
-10			

(b) Why do computers more often use 2's complement representation over 1's complement representation?

### Problem 6

(4 Points)

Convert the following 32-bit single-precision IEEE floating point number into decimal value. Show your work for full credit:

### 

The bits for the IEEE single-precision floating point number (N) are allocated as follows:

Sign (1 bit)	Exponent (8 bits)	Fraction (23 bits)

Where the value  $N = (-1)^{\text{Sign}} x 1$ .Fraction x 2 Exponent-127

Perform binary arithmetic for the following numbers as directed. All the numbers are represented in 2's complement form.

(a) Add the following 2's complement numbers. Write the final result as a 6-bit number.

- 010110
- + 1001

Did an overflow error occur in the previous addition? State how you know.

(b) Subtract the following 2's complement numbers. Write the final result as a 6-bit number.
 010011

 <u>010010</u>

Did an overflow error occur in the previous operation? State how you know.

(c) Convert the answers for (a) and (b) into decimal numbers. Show your work for full credit.

(a) Convert the following 3 hexadecimal numbers to unsigned binary. A 0x before a set of symbols (from 0 to F) indicates a hexadecimal number.

0x24

0xAA

0xD7

(b) Perform the specified logical operations on the following hexadecimal numbers. Write your result in unsigned binary. (Hint: first convert the hexadecimal to binary, which you did in part (a), and then perform the operations)

NOT(0x24 OR (0xAAAND 0xD7))

(c) Convert the result of part (b) into hexadecimal.

#### (4 points)

The ASCII table on the last page will be useful in solving this problem. You can detach it to make it easier to consult without flipping pages.

Consider two strings of two ASCII characters each: "**64**" and "**%**@". The ASCII characters in the string are the two characters between the quotation marks, and there is no null character terminating the string.

(a) First, convert each of these two strings into their corresponding 16-bit binary values.

(b) Now, suppose that the two 16-bit binary values were added as if they were signed integers in 2's complement, and the resulting 16 bits treated as if they were a string of ASCII characters. What would the resulting ASCII string be? Show your work for full credit.

#### Problem 10

#### (3 points)

Give an example of an *integer* that can be represented in floating point format (32-bit IEEE format), but cannot be represented as a 32-bit 2's complement integer. Show its 32-bit IEEE format representation.

Character	Hex	Character	Hex	Character	Hex	Character	Hex
nul	00	sp	20	@	40	`	60
soh	01	1	21	A	41	a	61
stx	02	**	22	в	42	b	62
etx	03	#	23	С	43	с	63
eot	04	s	24	D	44	đ	64
enq	05	%	25	Е	45	e	65
ack	06	&	26	F	46	f	66
bel	07	' (Apostr.)	27	G	47	g	67
bs	08	(	28	н	48	h	68
ht	09	)	29	I	49	i	69
lf	0A	*	2A	J	4A	j	6A
vt	0B	+	2B	К	4B	k	6B
ff	0C	, (Comma)	2C	L	4C	1	6C
cr	0D	-	2D	М	4D	m	6D
so	0E	. (Period)	2E	N	4E	n	6E
si	0F	7	2F	0	4F	0	6F
dle	10	0	30	Р	50	р	70
dc1	11	1	31	Q	51	q	71
dc2	12	2	32	R	52	r	72
dc3	13	3	33	s	53	s	73
dc4	14	4	34	Т	54	t	74
nak	15	5	35	U	55	u	75
syn	16	6	36	v	56	v	76
etb	17	7	37	W	57	w	77
can	18	8	38	x	58	x	78
em	19	9	39	Y	59	у	79
sub	1A	:	3A	Z	5A	z	7A
esc	1B		3B	[	5 <b>B</b>	{	7 <b>B</b>
fs	1C	<	3C	Λ	5C		7C
gs	1D	=	3D	]	5 <b>D</b>	}	7D
ſS	1E	>	3E	^	5E	~	7E
us	1F	?	3F	_ (Undrscre)	5F	del	7 <b>F</b>

ASCII Table