CS 536 — Spring 1998

CSX Code Generation Routines

Part III

CSX Class Body

We first generate the Jasmin class header declarations. A shared field `CLASS` is set to the name of the CSX class. Next, we generate field declarations. We then generate a method defintion for `main(String [])`, which is the standard starting point for JVM executions. This method contains non-trivial field initializations and a call to `main()`, the standard CSX starting point. Finially, methods are translated.

```
cg(){ //for classNode
   currentMethod = null; // We're not in any method body
   CLASS = CSXIdentifierToken.reg.toString(className.idval);
   // generate:
   //  .class public CLASS
   //  .super java/lang/Object

   // generate field declarations for the class
   members.fields.declField();

   // generate:
   //  .method public static main([Ljava/lang/String;)V

   // generate non-trivial field initializations
   members.fields.cg();

   // generate:
   //  invokestatic CLASS/main()V
   //  return
   //  .limit stack 2
   //  .end method

   // Fianlly translate methods
   members.methods.cg();
}
```

Methods

We'll assume that if we're currently translating an AST node that's within a method declaration (that is, "under" a `methodDeclNode`) then a shared field `currentMethod` points to that `methodDeclNode`. If we're not within a method declaration then `currentMethod` is `null`.

Calls are straightforward to translate. We first translate the parameter list, pushing each actual parameter onto the stack. We then "call" the appropriate method. Because Jasmin

requires that a method name in a call must contain type codes for the parameters and return value, we will require that each method, when translated, creates a field `methodTypeCode`, in its `SymbolInfo` node that contains this type code. Thus an integer function `f` that takes a single integer parameter, would have a code of "`f(I)I`".

```
cg(){ for argsNode
// Evaluate arguments and load them onto stack
   argVal.cg();
   moreArgs.cg();
}
```

```
cg(){ // for callNode
   // Evaluate args and push them onto the stack
   args.cg();

   // Generate call to method, using its type code
   genCall(methodName.idinfo.methodTypeCode);
}
```

The translation of `fctCallNodes` is essentially identical to that of `callNodes`.

Return statements within a function will evaluate the return value onto the stack and then do an `ireturn`. Return statements within a procedure generate a `return`.

```
cg(){ // for returnNode
   if (returnVal.isNull())
      // generate: return
   else { // Evaluate return value
      returnVal.cg();
      // generate: ireturn
}  }
```

Jasmin requires that a method name in a call must contain type codes for the parameters and return value, so we'll add a method `buildTypeCode`() to `argDeclsNode`, `argDeclNode` (as an abstract method), `valArgDeclNode` and `arrayArgDeclNode`. This will allow us to easily compute and store the necessary type code within a method.

```
String typeCode(typeNode type){
   // Return type code
   if (type instanceof intTypeNode)
      return "I";
   else if (type instanceof charTypeNode)
      return "C";
   else // (type instanceof boolTypeNode)
      return "Z";
}
```

```
String buildTypeCode() { // for argDeclsNode
    return buildTypeCode(thisDecl) + buildTypeCode(moreDecls);
}
```

```
String buildTypeCode() { // for valArgDeclNode
    return typeCode(argType);
}
String buildTypeCode() { // for arrayArgDeclNode
    return arrayTypeCode(argType);
}
```

Within methods, each parameter and local variable will be assigned a "local variable index," starting at zero. A field `numberOfLocals`, within a method's `SymbolInfo` node, will track how many locals have been allocated an index.

```
 cg(){ // for methodDeclNode
   currentMethod = this; // We're in a method now!
   methodName.idinfo.numberOfLocals = 0;
   String newTypeCode =
      CSXIdentifierToken.reg.toString(name.idval);
   if (args.isNull())
        newTypeCode = newTypeCode + "()";
   else newTypeCode =
        newTypeCode + "(" + args.buildTypeCode() + ")";
   if (returnType.isNull())
        newTypeCode = newTypeCode + "V";
   else newTypeCode =
        newTypeCode + typeCode(returnType);
   methodName.idinfo.methodTypeCode = newTypeCode;
   // generate:
   //   .method public static newTypeCode

   args.cg(); // Assign local variable indices to args
   // Generate code for local decls and method body
   decls.cg();
   stmts.cg();

   // generate default return at end of method body
   if (returnType.isNull())
      // generate: return
   else { // Push a default return value of 0
      loadI(0);
      // generate: ireturn;
   }
   // generate end of method data
   // we'll guestimate stack depth needed at 25;
   //   (almost certainly way too big)
   // generate: .limit stack 25
   // generate: .limit locals methodName.idinfo.numberOfLocals
   // generate: .end method
}
```

```
cg(){ // for argDeclsNode
// Label each method argument with its address info
   thisDecl.cg();
   moreDecls.cg();
}

cg(){ // for valArgDeclNode
// Label method argument with its address info
   argName.idinfo.adr = local;
   argName.idinfo.varIndex =
      currentMethod.name.idinfo.numberOfLocals++;
}

cg(){ // for arrayArgDeclNode
// Label method argument with its address info
   argName.idinfo.adr = local;
   argName.idinfo.varIndex =
      currentMethod.name.idinfo.numberOfLocals++;
}
```

We need to extend `varDeclNode`, `constDeclNode` and `arrayDeclNode` to handle local variables.

```
cg(){ // for varDeclNode
   if (currentMethod == null) { // A global var declaration
   // Same as defined previously
      if(!(initValue.isNull()) &&
         !(initValue instanceof intLitNode) {
        // compute and assign initial value
         initValue.cg();
         storeId(varName);
   }  }
   else {  // A local var declaration
      varName.idinfo.adr = local;
      varName.idinfo.varIndex =
             currentMethod.name.idinfo.numberOfLocals++;
      if(!initValue.isNull()) { // assign init value
         initValue.cg();
         storeId(varName);
}  }  }
```

```
cg(){ // for constDeclNode
    if (currentMethod == null) { // A global const declaration
    // Same as defined previously
       if(!(constValue instanceof intLitNode) {
       // compute and assign initial value
       constValue.cg();
       storeId(constName);
    }  }
    else { // A local const
       constName.idinfo.adr = local;
       constName.idinfo.varIndex =
          currentMethod.name.idinfo.numberOfLocals++;
       constValue.cg();
       storeId(constName);
}   }


cg(){ // for arrayDeclNode
   // Create a new array and store resulting reference
   if (currentMethod != null) { // A local array declaration
      arrayName.idinfo.adr = local;
      arrayName.idinfo.varIndex =
          currentMethod.name.idinfo.numberOfLocals++;
   }
   // Now create the array & store a reference to it
   loadI(arraySize.intval); // Push number of array elements
   allocateArray(elementType);
   if (arrayName.idinfo.adr == global)
        storeGlobalReference(arrayName.idinfo.label,
                             arrayTypeCode(elementType));
   else storeLocalReference(arrayName.idinfo.varIndex);
}
```

Finally, we handle blocks.

```
cg(){ // for blockNode
   // Generate code for block decls and body
   decls.cg();
   stmts.cg();
}
```